

MEGA^{LITE}

DRAMA^{ZW200}
LED



USER MANUAL

Table of Contents

Safety Information.....3

Specifications.....4

Main Power Connection.....5

DMX-512 Connection.....5

DMX Profile6

Main Control Menu.....7

Rigging the Fixture.....8

Cleaning & Maintenance.....8

Parts List.....8

Check that the unit has not been damaged during transport



Read all cautions and warnings
prior to operation of this
equipment

Protection Against Fire



Fire

1. Maintain a minimum of 1 foot distance from any type of flame.
3. Replace fuse only with the specified type and rating.
4. Do Not install the unit too close to a heat source.
5. Make sure cables are properly secured away from unit movement.
6. Maximum surface operating temperature 104°.

Protection Against Fire



Electrical

1. Disconnect power before servicing.
2. For connection to main power supply proceed to page 5.
3. This unit must be earthed. (electronically grounded)
4. Do not expose unit to rain or moisture.

Protection Against Mechanical Hazards



Mechanical

1. Use safety chain when hanging unit.
2. Use quality clamps or bolts when positioning unit
3. Do not open unit while it is on, risk of electrical shock.

Technical Information

Part Numbers

Fixture

7035-CW	Drama Z Wide Cool White 200 Cool White
7035-WW	Drama Z Wide Warm White 200 Warm White
7030-GH	Removable Gobo Holder (accessory included)
7030-JH	Removable Gel Holder (accessory included)

Mechanical Specifications

DMX Connectors:	3 and 5 pin XLR connectors in/out
Power Connections:	Neutrik Power con In and Out
Power Cable:	4 Ft 7 Inch PowerCon to Nema 5-15 Cable
Thermal:	Maximum ambient temperature 104° Maximum surface temperature 140°
Display:	Digital LED
Fastening System:	Mounting Yoke


Fixture	Packaged for Shipping
Size: 25"L x 10.5"W x 16.16"H Weight: 22 lbs	Size: 31" X 12.5" X 12.5" Weight: 25 lbs

Electrical Specifications

LED Type:	1 COB LED
LED Watts:	200
LED Color Temp:	CW= Cool White 5600K WW= Warm White 3200K
CRI:	≥85Ra
LED AVG Lifetime:	60,000 to 100,000 hours
Zoom:	Manual Zoom from 20° to 45°
Fan:	Heat Pipe Cooling with low noise fan
Power Consumption:	Universal 100 - 240V 50/60 Hz
Ballast:	Electronic
Power Consumption	Watts: 242 Amps: 2.12

Control & Programming

Protocol:	DMX 512
DMX Channels:	2 Operating Modes 1 Channel Dimmer, 2 Channel Dimmer, Strobe
Operating mode:	Stand alone 255 step Dimmer setting via display.





Main Power Connection

Caution!


- 1. Do not connect fixture to a dimmer system.
- 2. This unit has Auto switching power supply. It will respond to 110V or 220V automatically
- 3. This unit must be earthed. (electronically grounded)
- 4. Replace fuse only with the specified type and rating.

The occupation of the connection-cable is as follows:


This fixture is equipped with an electronic power supply that will let the unit operate from 100V to 240V from 50Hz to

Cable (USA)	Cable (EU)	Pin	110V	220V
Black	Brown	Live	L	L
White	Light Blue	Neutral	N	L
Green	Yellow/Green	Ground		

110V—Connection




220V—Connection



DMX-512 Connection


The fixture is equipped with 3 pin XLR Sockets for DMX input and output. The sockets are wired in parallel. Only use a shielded twisted pair cable designed for RS-485 and 3 pin XLR plugs and connectors in order to connect the controller with the fixture or the fixture with another.

DMX—input



1. Shield
2. Signal (-)
3. Signal (+)
4. N/A
5. N/A

DMX—output



Caution!

At the last fixture the DMX signal needs to be terminated with a terminator. Solder a 120 Ohm resistor between the (-) and the (+) signal into a 3 pin XLR plug and plug it in to the last fixture on the signal run. Pre-manufactured terminator plugs are available for purchase from your Mega-Lite dealer (P-DMXT).

DMX Profile

Drama Z 200 W Mode 1 CH


DMX Chanel	Function	Description	Value
1	Dimmer	LED intensity	0-255

Drama Z 200 W Mode 2 CH

DMX Chanel	Function	Description	Value
1	Dimmer	LED intensity	0-255
2	Strobe	No Function	0
		Strobe (slow to fast)	1-127
		Pulse On (slow to fast)	128-159
		Pulse Off (slow to fast)	160-191
		Random Strobe (slow to fast)	192-255

Main Control

The control board on the fixture base is your interface to access and control all the functions on the unit. It's digital display gives you a code view of the options and functions. The following will explain each function and its options.



<div>Address 001</div>	<p>This function allows you to set your DMX Start Channel. First make sure you have a proper DMX connection from your controller using the 3 or 5 pin XLR connection. If there is no DMX connection the red LED indicator will flash. If there is proper DMX connection the red LED indicator will be off.</p> <p>To Set the DMX Start Channel press Enter. Use the Down or Up to select the desired DMX Start Channel and press Enter to confirm your setting.</p>
<div>Reset Function</div>	<p>To reset the fixture press Enter. Use the Up or Down for Yes or No press Enter to confirm your setting.</p>
<div>Master Function</div>	<p>This function allows the unit to output DMX signal to operate the same as the Master unit. All preset settings will be copied the other fixtures.</p> <p>Press Enter. Use the Up or Down for Yes or No press Enter to confirm your setting.</p> <p>Note: All other fixtures must be connected via XLR Connection. And must be put on DMX address Channel 001</p>
<div>Perform Function</div>	<p>This function allows the unit to activate the built in programs.</p> <p>Press Enter. Use the Up or Down for 000,001 or 002 press Enter to confirm your setting.</p> <p>You can record a scene by selecting the performance function you want to use from 0 to 2. Then accessing the ManDim function and setting the desired intensity then press Enter to confirm.</p>
<div>Channel Mode</div>	<p>The fixture was a capability to operate in 2 different modes of DMX control. Mode 1CH is Dimmer , Mode 2CH is Dimmer and Strobe</p> <p>Press Enter. Use the Up or Down for 1CH or 2CH press Enter to confirm your setting.</p>
<div>ManDim 000</div>	<p>This function let you set the Dimmer intensity via display.</p> <p>Press Enter. Use the Up or Down from 000 to 255 press Enter to confirm your setting.</p>
<div>Version 000</div>	<p>Operating Software</p>

Rigging the fixture

Caution!

1. The installations must be carried out by an authorized dealer or trained professional.
2. Unit may cause severe injuries if you have doubts concerning the safety do not install.

When rigging a unit it is very important that you follow common safety procedures. Rigging requires extensive experience including but not limited to calculating working loads, material being used and periodic safety inspections. If you lack these qualifications, do not attempt the installation yourself, instead use a professional structural rigger.

When rigging the unit always be secured with a secondary safety attachment. The installation location of the projector has got to be built in the way that it can hold 10 times the weight for 1 hour without any harming. Installation should be checked at least one time a year by a skilled person.

Cleaning and maintenance

Installation Maintenance: The operator has to make sure that the unit is operating safely and has the installations and electronics checked by an expert every 2 years.

The following points have to be considered during the inspection:

- 1) All screws used for installing the device or part of the device have to be tightly connected and must not be corroded.
 - 2) There must not be any deformations on the housing, fixation and installation spots (ceiling, suspension, trussing).
 - 3) The electronic power supply cables must not show any damages, material fatigue (e.g. porous cables) or sediments.
- Further instructions depending on the installation spot and usage have to be adhered by a skilled installer and any safety problems have to be removed.

Note: There is no serviceable parts inside the device except for the LED's. Maintenance and service operations are to be carried out by authorized dealers.

Replacing the fuse: Only replace the fuse with the same type and rating. F3.15AL250

Replacing the power cable: If the power cable of this device becomes damaged, it has to be replaced by authorized dealers or trained professional only.

Should you have further questions , please contact your dealer.

Parts List

7025-FAN	Large Replacement fan
7030-MPCB	Main PCB card
7030-PS	Power Supply
7030-DIS	Display
7025-FB	Front Bessel Plastic Replacement
7025-RB	Rear Bessel Plastic Replacement
7030-FL	Front lens
7025-KNOB	Knob Set

7030-GH	Removable Gel Holder
7030-GEH	Removable Gel Holder

Warranty Information

Warranty Conditions

- Unless otherwise stated in writing, your product is covered by a one year parts and labor limited warranty.
- LEDs are not guaranteed to match in color temperature or output.
- It is the owner's responsibility to furnish receipts or invoices for verification of purchase, date, and reseller or distributor. If purchase date cannot be provided, date of manufacture will be used to determine warranty period.
- Goods returned under warranty must follow the proper authorization procedure and must be accompanied by a copy of the original invoice.
- Goods repaired under warranty will be returned to the owner with the freight prepaid by MSI via the most economical means of shipment.
- Repair or replacement as provided for under this warranty is the exclusive remedy of the consumer. MEGA SYSTEMS INC. makes no warranties, express or implied, with respect to any product, and Mega Systems specifically disclaims any warranty of merchantability or fitness for a particular purpose. Mega Systems shall not be liable for any indirect, incidental or consequential damage, including lost profit, sustained or incurred in connection with any product or caused by product defect or the partial or total failure of any product regardless of the form of action, whether in contract, tort (including negligence), strict liability or otherwise, and whether or not such damage was foreseen or unforeseen.
- Warranty is void if the product is misused, damaged, modified in any way, or for unauthorized repairs or parts. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.



Mega-Lite
5718 Kenwick St
San Antonio, TX 78238
Ph 210-684-2600 Fax 210-855-6279
www.mega-lite.com / info@mega-lite.com